


LED Candle 4W 100-240V CRI>80 250LM Non-Dim E14

| 1 Product Information | | | | | |
|-------------------------------|---------------------------|---|-----|--|---------|
| 1-1 | Product Description | LED Candle 4W 100-240V CRI>80 250LM Non-Dim E14 | |  | |
| 1-2 | Primary Region | North America and Canada | | | |
| 1-3 | Primary Application | Household, Church, School, Shopping Center | | | |
| 1-4 | Primary Replacement | 40w | | | |
| 1-5 | Warranty | 5 Years | | | |
| 1-6 | Environmental(RoHS/REACH) | Rosh | | | |
| 1-7 | Certificates | NOM-030 | | | |
| 2 Product Specification | | | | | |
| 2-1 | Lamp Type | LED Candle lamp | | | |
| 2-2 | Dimmable (Y/N) | N | | | |
| 2-3 | Base/Cap | E14 | | | |
| 2-4 | Lamp Wattage | 4W | | | |
| 2-5 | Life time | 15,000hrs | | | |
| 2-6 | Operating Temperature | -20/45°C | | | |
| 2-7 | Environmental Rating | Damp Location | | | |
| 2-8 | Size(WxH) | 35x105 mm | | | |
| 2-9 | Material | Metal and Plastic | | | |
| 2-10 | Weight (kg) | 0.03kg (0.066 lb) | | | |
| 3 Photometric Characteristics | | | | | |
| 3-1 | Nominal Lumens | 250lm | 3-5 | Color Rendering Index | >80 |
| 3-2 | Beam Angle | 270° | 3-6 | R9 | >0 |
| 3-3 | Initial Lumens per Watt | ≥62 | | | |
| 3-4 | Color Temperature | 3000K | | | |
| 4 Electrical Characteristics | | | | | |
| 4-1 | Rated Voltage/Frequency | 100-240V, 50/60 Hz | 4-3 | Power Factor | >0.4 |
| 4-2 | Lamp rated Wattage | 4W | 4-4 | Dimming Range in % | N |
| 5 LED Information | | | | | |
| 5-1 | Chip Manufacturer | Bridgelux | 5-2 | LED model | 2835 |
| 6 Package | | | | | |
| 6-1 | Color Box Size (mm) | 36x36x108mm | 6-2 | Q'ty per Box (pcs) | 1 pc |
| 6-3 | Master Carton Size (mm) | 385x200x242mm | 6-4 | Q'ty per Carton (pcs) | 100 pcs |
| 6-5 | Net weight(kg) | 3.3kg | 6-6 | Gross Weight(kg) | 4.78kg |

